TIMETRAX™ Sync Tone ○ Q

110-Volt Ethernet Tone Generator

SIMPLE ○ SMART®

Time Optimization.

TimeTrax™ Sync ToneQ Ethernet Tone Generator improves accountability & productivity by promoting standardized shift changes, arrival, break & dismissal times. Use in schools for perfectly synchronized class changes & school or district-wide bus waves. TimeTrax™ Sync tone scheduling software allows you to manage & customize synchronized tone scheduling right from your PC. Ideally suited for K-12 schools, manufacturing plants, distribution centers & correctional facilities.

SEDSTSLAUB Tone-Q,
110-Volt Ethernet Tone Generator

- Fully automated Ethernet based timed alert tone system for signaling shift changes, class changes, breaks or emergencies

- Create, customize & manage tone sequence schedule using TimeTrax™ Sync Tone-Q software

- Use in conjunction with TimeTrax™ Sync wall clocks for facility-wide synchronization

- Easily define & set holiday, seasonal & assembly schedules

- Allows schedule modification & suspensions

- Direct schedule upload enables independent operation

- Manages up to 4 independent contacts/zones to control tones

- Stores .wav or .mp3 audio files up to a total of 150 seconds

- Interfaces with internal PA System

scan

Smart.
scan QR code for industry solutions

MADE IN USA

TT Sync Digital Clock : Education : Corporate : Manufacturing : Healthcare : Transportation : Government

PYRAMID

♫ TONE Q SPECIFICATIONS

|	
Part Number	SEDSTSLAUB
Time Source	NTP Server
Timed Event Capacity	1000
Independent Contacts/Zones	4
Tone File Format	.wav or .mp3 (up to150 seconds)
Operating Temp	-30˚F (-34.44˚C) to 130˚F (54.44˚C)
Display	LCD, time & date
Housing	Textured powder coat surface metal
Color	Black
Mounting	Wall Mount
Warranty	3-Year manufacturer's limited warranty
Guarantee	30-Day money back guarantee
UL Listed	Power Supply
Compliance	FCC, part 15, section 15, 247 FCC ID# WC7H9ALG1
Includes	TimeTrax™ Tone-Q, TimeTrax™ Sync software (SASDLCWDXX), 20ft Cat5E Cable, Transformer & Quick Start Guide
Power Input	105-240V AC
Power Consumption	<2W
Dimensions	5.625inW (14.28cm) x 6.5inH (16.51cm) x 1.75inD (4.44cm)
Weight	1.75lbs (.79kg)
Shipping Weight	3.5lbs (1.58kg)

Ethernet   Tone   Wall Clock Interface   Synchronize   Expandable

SEDSTSLAUB Tone-Q

.5in
6.5in
5.625in
1.75in

POWER   GPS-AUX   ETHERNET

power configuration

ZONES 1 2 3 4   BCD OUT   PHONE OUT   AUDIO OUT OUT-BAL VOL

zone/audio configuration